



BOWELL EFGC FLAIL MOWER

For Small & Medium Tractors With CAT I. & II. 3-Point-Hitch



- ✚ Up to a grass height of approx. 75 cm
- ✚ 135 / 155 / 175 / 195 cm working width
- ✚ For 25 - 65 HP tractor



BOWELL EFGC FLAIL MOWER

Middle duty flail mower with 800 g flail hammers for small and medium sized tractors from 25 hp to 65 hp with CAT I/II 3-point hitch.



Forged
Flail Hammers

24 months
Warranty

12 months for commercial customers



included

€ ab 1.448



The Bowell EFGC flail mowers complies with all safety regulations and is CE tested following the 2006/42/EC machine directive.

Working widths of 135 / 155 / 175 / 195 cm





The Bowell EFGC flail mower series comes with a reinforced free-wheel transmission from Comer Italy. With an available working width of up to 195 cm the massive EFGC flail mowers can be perfectly adjusted to the power and width of your tractor and the job that needs to be done.

- 1 Transmission from COMER Italy.
- 2 All outside nuts and bolts are DACROMET coated.
- 3 Rotor shaft with SKF ball bearings and CNC bearing seats.
- 4 Stainless steel grease nipples.
- 5 Easy testing of belt tension with out tools.
- 6 Replaceable counter knives.



Technical Specifications Bowell EFGC Mower

DATA	EFGC-135	EFGC-155	EFGC-175	EFGC-195
Dimensions (LxWxH)	162 x 94 x 84 mm	182 x 94 x 84 mm	202 x 94 x 84 mm	222 x 94 x 84 mm
Total weight incl. PTO shaft	296 kg	313 kg	336 kg	360 kg
Working width	1350 mm	1550 mm	1750 mm	1950 mm
Adjustable mowing height	20 – 75 mm			
Recommende grass height	< 70 cm			
3-point hitch tractor	Cat I (Cat II bushings included)			
PTO clockwise	540 RPM / 1000 RPM			
PTO length	1000 mm			
Working performance (approx.)	5400 - 10800 m ² /h	6200 - 12400 m ² /h	7000 - 14000 m ² /h	8800 - 15600 m ² /h
No. of belts / width	3 / 17 mm	3 / 17 mm	4 / 17 mm	4 / 17 mm
Recommended tractor HP	25-40 HP	30-40 HP	40-55 HP	45-65 HP
Material strength housing	4 mm			
Material strength side walls	6 mm			
Painting	powder coating			
Flail type	hammer			
No. of flails	24	24	28	32
Weight per flail	800 g			
RPM of rotor shaft	2200			
Diameter / wall strength rotor shaft	108 mm / 8 mm			
Diameter / wall strength rear roller	133 mm / 4 mm			
Wooden transport box (LxWxH)	170 x 105 x 84 cm	190 x 105 x 84 cm	210 x 105 x 84 cm	230 x 105 x 84 cm



	A1 (mm)	B1 (mm)	C1 (mm)	D1 (mm)	E1 (mm)	F (mm)	G (mm)	A2 (mm)	B2 (mm)	C2 (mm)	D2 (mm)	E2 (mm)
EFGC135	754	608	454	600	308	641	421	604	758	304	600	458
EFGC155	954	608	654	600	308	641	421	804	758	504	600	458
EFGC175	1154	608	854	600	308	641	421	1004	758	704	600	458
EFGC195	1354	608	1054	600	308	641	421	1204	758	904	600	458



ONLINE-SHOP FOR TRACTOR ATTACHMENTS

Flail Mower, Verge Mower, Power Sprayer, Boom Sprayer, Back Hoe and Snow Blades



Contact

Telefon: + 49 (0) 4188 4444 773

E-mail: info@bowell-tractor.com

V&B Europe GmbH

Am Flidderberg 74

D-21256 Handeloh - Germany